

PAG-114




4 Ports DisplayPort 1.1 KVM Switch with USB 2.0, Hotkey Control

Specifications

Model Number	PAG-114	
MAX. Resolution	2560x1600@60Hz (4:4:4)	
Interfaces	PC Side	Console Side
Video Switching	DP 1.1 x 2 (In)	DP 1.1 x 1 (Out)
USB Switching	USB 2.0 x 2 (B)	USB HID x 2 (A) USB 2.0 x 2 (A)
Control Methods	Hotkey / Push Button	
HDCP Compliance	HDCP 1.4	
Hot Plug-and-Play	Yes	
Push Buttons	Port-Select x 4	
LED Indicators	PC-Ready x 4, PC-Select x 4, Power x 1	
Power supply	DC 9~12V	
Operation Environment	0~40°C, Humidity<80%	
Storage Temperature	-20~60°C	
H x W x D (mm)	44 x 220 x 130	
Material	Metal	
Weight (g)	1150	

Features

- Allows 4 Computers Share 1 Set of KVM Console
- **Most Popular Resolutions Supported** by DP 1.1 Video Up to QHD@60Hz (4:4:4)
- Flexible Control Methods Suits Variable Scenarios :
 - **Push Button**
 - **Keyboard Hotkey**
- **Hotkey Control** Allows Fast Switching via USB Keyboard Commands
- **USB 2.0** Sharing Ports Supports Most Devices
- **Independent Switching** of USB 2.0
- **HDCP 1.4 Compliance** Ensures Uninterrupted Video Playback
- **Plug-n-Play**, No Driver or Software Required
- **Brackets** Available for Rack Install
- **Medical / Radar / Gaming / Office Applications**



USB 2.0

Hotkey Control

Product Family

2-Port Models	4-Port Models	Video	Multi-Monitor	USB
PAAG-Z112	PAAG-Z114A	DisplayPort 1.2 (MAX. 4K)	Single	KM Only
PADG-Z122	PADG-Z124A		Dual	
PADG-Z132	PADG-Z134A		Triple	
PADG-Z142	PADG-Z144A		Quad	
PAAG-112	PAAG-114A	DisplayPort 1.2 (MAX. 4K)	Single	480Mbps
PADG-122	PADG-124A		Dual	
PADG-132	PADG-134A		Triple	
PADG-142	PADG-144A		Quad	

*Certain Models Available Upon Bulk Orders

**USB 3.2 Models Also Available

***8K DisplayPort 1.4 Models Also Available

Connection pattern

