

KAAG-112



2-Port VGA KVM Switch w/ Audio & Hotkey Control

► Specifications

		KAAG-112
Console Port		1
Computer Port		2
Front Panel Push Button		1
Automatic Scan Interval		3, 8, 15, 30 Seconds
Cable Length (Max)		3M (10ft) for USB
Computer ON-LINE LED		2
Computer Selected LED		2
Hot Plug-and-Play		Yes
Console Interface	USB Port	4 (KB+MS+Extra USB 2.0)
	KB	USB
	MS	USB
	Monitor	HDB15-F
Computer Interface	Audio Jack	1 Set
	KB	USB
	MS	
	Monitor	HDB15-M
	Audio Jack	2 Set
Hotkey		Yes
OSD		No
Resolution		UXGA(1600 x 1200), WUXGA(1920 x 1200)
DDC2B		Yes
H x W x D (mm)		44 X 160X 100

► Features

- Support Audio function
- Support USB console
- 2 computers share up to 4 different USB peripherals (KB + MS + USB 2.0 Devices)
- Support Video with the resolution up to UXGA(1600x 1200)/ WUXGA(1920 x 1200)
- Unique Tracking System enable the USB devices to operate independently
- USB 2.0 peripheral sharing eliminates the expense of duplicate devices
- Front panel push buttons for easy computer selection
- No drivers needed for keyboard and mouse operation
- Support keyboard and mouse plug-n-play
- Buzzer sound for computer switching confirmation
- Hotkey functions allow easily computer access
- Support Windows and Mac host systems
- No software required

► Connection Pattern

