

# UCNV-104D

## USB+PS/2 KVM Switch

### ► Specifications

		UCNV-104D
Number of Console Ports		1
Number of Computer Ports		4
Control Buttons on Front Panel		4
Applicable to computer		PS/2 PC, USB PC, USB-Sun, USB-Mac
On-Screen Display (OSD)		Yes
Plug-n-Play		Yes
Hotkey Control		Yes
Computer Name Entry		14-Character
Auto-Scan Interval		3, 8, 15, 30 Seconds
Programmable Scan Pattern		Yes
Security Control		4-Character Password Per Computer
Cable Type		1-to-3 (PS/2) or 1-to-2 (USB) Cable Max 30M (100ft) at PC ports for PS/2 computer Max 5M at PC ports for USB computer
Video Resolution		1920 x 1440, DDC2B
Computer Connectors		HDB15 Female (Grey) x 4 for PS/2 + USB Interface
Console Connectors	Keyboard Mouse Monitor	USB mouse x 1 USB keyboard x 1 HDB15 monitor female x 1
Size		1U
Power Consumption (Max.)		9V DC, 500mA
Dimensions H x W x D (mm)		44 x 220 x 130

### ► Features

- Support both USB and PS/2 interface (PC)
- Cascade configuration expands system capability
- 1U-height form factor saves rack spaces
- Unique cables for secured connection
- Auto-scan function automatically selects computer sequentially
- Assigns computers with unique and meaningful names
- Identifies and selects computers by the names
- Programmable scan filters unused computers
- Stores system settings and name entries to non-volatile memory
- Password security locks computer from unauthorized access
- Complete control with easy-to-use OSD interface
- Hotkey functions allow easily computer access
- Keyboard states automatically saved and restored while switching computers
- Operating system is independent and transparent to all applications
- Plug-and-play system configuration
- Supports screen resolutions of up to 1920 x 1440
- DDC2B compatible
- Supports SUN keyboard emulation

### ► Connection Pattern

